

Reset Engine Oil Replacement Reminder Light

2009 Model Year Toyotas

Model	Reset Reminder Light Procedure
'09 Avalon Page 325	After changing the engine oil (U.S.A. only) The oil change system should be reset. Perform the following procedures: <ol style="list-style-type: none">1. Switch the display to the odometer. (Page 142)2. Turn the "ENGINE START STOP" switch or the engine switch OFF.3. Vehicles with smart key system: While pressing the trip meter reset button, turn the "ENGINE START STOP" switch to IGNITION ON mode. Continue to press and hold the button until the trip meter displays 000000. Vehicles without smart key system: While pressing the trip meter reset button, turn the engine switch to the "ON" position. Continue to press and hold the button until the trip meter displays 000000.
'09 Camry Page 323	Changing the engine oil (U.S.A. only) To reset the oil change system, follow the procedure below: <ol style="list-style-type: none">1. Turn the "ENGINE START STOP" switch or engine switch OFF with the trip meter A reading shown. (Page 149)2. While pressing the trip meter reset button (page 141), turn the "ENGINE START STOP" switch or engine switch ON.<ul style="list-style-type: none">▶ Without multi-information display3. Continue to press and hold the knob until the trip meter displays 000000.<ul style="list-style-type: none">▶ With multi-information display3. Continue to press and hold the knob until "COMPLETE" appears on the multi-information display.
'09 Camry Hybrid Vehicle Page 295	After changing the engine oil (U.S.A. only) To reset the oil change system, follow the procedure below: <ol style="list-style-type: none">1. Turn off the hybrid system with the trip meter A reading shown. (Page 145)2. The "POWER" switch must be set in ON mode while holding down the trip meter reset knob. A message "OIL MILEAGE RESET MODE" will appear on the display.3. Hold down the knob at least 5 seconds. A message "COMPLETE" will appear and the message "OIL MILEAGE RESET MODE" goes off.

Reset Engine Oil Replacement Reminder Light

2009 Model Year Toyotas

Model	Reset Reminder Light Procedure
'09 Corolla Page 315	After changing the engine oil (U.S.A. only) The engine oil maintenance data should be reset. Perform the following procedures: <ol style="list-style-type: none">1. Turn the "ENGINE START STOP" switch or engine switch OFF with the trip meter A reading shown.2. While pressing the trip meter reset button (page 138), turn the "ENGINE START STOP" switch or engine switch ON.3. Continue to press and hold the button until the trip meter displays 000000.
'09 FJ Cruiser Page 294	After changing the engine oil (U.S.A. only) The oil change system should be reset. Perform the following procedures: <ol style="list-style-type: none">1. Turn the engine switch off with the odometer reading shown (page 135)2. Turn the engine switch to the ON position while holding down the trip meter reset button.3. Continue to press and hold the button until the odometer displays 000000. If the system fails to reset, the light will remain flashing.
'09 Highlander Page 436	Changing the engine oil (U.S.A. only) To reset the oil change system, follow the procedure below: <ul style="list-style-type: none">▶ Vehicles without smart key system.<ol style="list-style-type: none">1. Set the engine switch to the "LOCK" position with the trip meter A reading shown. (page 185)2. While pressing the trip meter reset button, set the engine switch to the "ON" position.▶ Vehicles with smart key system.<ol style="list-style-type: none">1. Set the "ENGINE START STOP" switch OFF with the trip meter A reading shown. (page 185)2. While pressing the trip meter reset button, set the "ENGINE START STOP" switch to the IGNITION ON mode.3. Without multi-information display: Continue to press and hold the button until the trip meter displays "000000".3. With multi-information display: Continue to press and hold the button until "COMPLETE" appears on the multi-information display.

Reset Engine Oil Replacement Reminder Light

2009 Model Year Toyotas

Model	Reset Reminder Light Procedure
<p>'09 Highlander Hybrid Vehicle</p> <p>Page 437</p>	<p>Changing the engine oil (U.S.A. only)</p> <p>To reset the oil change system, follow the procedure below:</p> <ol style="list-style-type: none"> 1. Set the "POWER" switch OFF with the trip meter A reading shown. (page189) 2. While pressing the trip meter reset button, set the "POWER" switch in ON mode. 3. Continue to press and hold the button until "COMPLETE" appears on the multi-information display.
<p>'09 Landcruiser</p> <p>Page 394</p>	<p>Resetting the engine oil maintenance data</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none"> 1. Switch the display to the trip meter A when the engine is running. (Page 165) 2. Turn the "ENGINE START STOP" switch OFF. 3. While pressing the trip meter reset button, set the "ENGINE START STOP" switch to IGNITION ON mode (but do not start the engine because otherwise the reset mode will be cancelled). Continue to press and hold the button until the multi-information display indicates that the reset is complete.
<p>'09 Matrix</p> <p>Page 293</p>	<p>After changing the engine oil (U.S.A. only)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none"> 1. Turn the engine switch off with the trip meter A reading shown. 2. While pressing the trip meter reset button (page 119), turn the engine switch to the "ON" position. 3. Continue to press and hold the button until the trip meter displays 000000.
<p>'09 Prius</p> <p>Page 365</p>	<p>Resetting the engine oil maintenance data (U.S.A. only)</p> <p>Perform the following steps:</p> <ol style="list-style-type: none"> 1. Turn the "POWER" switch to OFF mode with the odometer shown. 2. Turn the "POWER" switch to ON mode with the trip meter reset button (page 146) held down. 3. Keep pressing the button for longer than 5 seconds after the "POWER" switch is in ON mode. <p>When the odometer indicates "000000" and the light goes off, the system reset is completed.</p>

Reset Engine Oil Replacement Reminder Light

2009 Model Year Toyotas

Model	Reset Reminder Light Procedure
<p>'09 RAV4</p> <p>Page 358</p>	<p>Changing the engine oil (U.S.A. only)</p> <p>To reset the oil change system, follow the procedure below:</p> <ul style="list-style-type: none"> ▶ Vehicles without smart key system. <ol style="list-style-type: none"> 1. Turn the engine switch off with the trip meter A reading shown. (page 156) 2. While pressing the trip meter reset button, turn the engine switch to the "ON" position. 3. Press and hold the button until the trip meter displays "000000". ▶ Vehicles with smart key system. <ol style="list-style-type: none"> 1. Turn the "ENGINE START STOP" switch off with the trip meter A reading shown. (page 156) 2. While pressing the trip meter reset button, turn the "ENGINE START STOP" switch to IGNITION ON mode. 3. Press and hold the button until the trip meter displays "000000".
<p>'09 Sequoia</p> <p>Page 455</p>	<p>After changing the engine oil (U.S.A. only)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none"> 1. Turn the engine switch off with trip meter A reading shown. 2. While pressing the trip meter reset button (page 161), turn the engine switch on. <ul style="list-style-type: none"> ▶ Without multi-information display <ol style="list-style-type: none"> 3. Continue to press and hold the button until the trip meter displays 000000. ▶ With multi-information display <ol style="list-style-type: none"> 3. Continue to press and hold the button until "MAINT REQD RESET MODE COMPLETE" appears on the multi-information display.
<p>'09 Sienna</p> <p>Page 442</p>	<p>Changing the engine oil (U.S.A. only)</p> <p>To reset the oil change system, follow the procedure below:</p> <ol style="list-style-type: none"> 1. Turn the engine switch to the "ACC" or "LOCK" position with the odometer reading shown. (page 174) 2. While pressing the trip meter reset button, turn the engine switch to the "ON" position. 3. Continue to press the button until the trip meter displays "000000".

Reset Engine Oil Replacement Reminder Light

2009 Model Year Toyotas

Model	Reset Reminder Light Procedure
<p>'09 Tacoma</p> <p>Page 361</p>	<p>After changing the engine oil (U.S.A. only)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none"> 1. Turn the engine switch off with the odometer reading shown. (Page 150) 2. Turn the engine switch to the ON position while holding down the trip meter reset button. 3. Continue to press and hold the button until the odometer displays 000000. <p>If the system fails to reset, the light will continue flashing.</p>
<p>'09 Tundra</p> <p>Page 483</p>	<p>After changing the engine oil (U.S.A. only)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none"> 1. Turn the engine switch off with trip meter A reading shown. 2. While pressing the trip meter reset button (page 190), turn the engine switch on. <ul style="list-style-type: none"> ▶ Without multi-information display 3. Continue to press and hold the button until the trip meter displays 000000. <ul style="list-style-type: none"> ▶ With multi-information display 3. Continue to press and hold the button until "MAINT REQD RESET MODE COMPLETE" appears on the multi-information display.
<p>'09 Venza</p> <p>Pages 450 & 451</p>	<p>After changing the engine oil (U.S.A. only)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none"> 1. Switch the display to the trip meter A when the engine is running. (Page 179) 2. Vehicles with smart key system: Turn the "ENGINE START STOP" switch off. Vehicles without smart key system: Turn the engine switch to the "LOCK" position.

Reset Engine Oil Replacement Reminder Light

2009 Model Year Toyotas

Model	Reset Reminder Light Procedure
<p>'09 Yaris Hatchback</p> <p>Page 249</p>	<p>After changing the engine oil (except Canada)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none">1. Turn the engine switch off with the trip A reading shown. (Page 137)2. Turn the engine switch to the ON position while holding down the trip meter reset button.3. Continue to press and hold the button until the trip meter displays 000000. <p>If the system fails to reset, the light will continue flashing.</p>
<p>'09 Yaris Sedan</p> <p>Page 232</p>	<p>After changing the engine oil (except Canada)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none">1. Turn the engine switch off with the Trip A reading shown. (Page 117)2. Turn the engine switch to the ON position while holding down the ODO/TRIP button.3. Continue to press and hold the button until the trip meter displays 000000. <p>If the system fails to reset, the light will continue flashing.</p>
<p>'09 4Runner</p> <p>Page 378</p>	<p>After changing the engine oil (U.S.A. only)</p> <p>The oil change system should be reset. Perform the following procedures:</p> <ol style="list-style-type: none">1. Turn the engine switch to the ACC or LOCK position with the odometer reading shown. (Page 148)2. Turn the engine switch to the ON position while holding down the trip meter reset button.3. Hold down the button until the light goes off. Before the light goes off, it illuminates for 3 seconds, flashes for 2 seconds and illuminates for 1 second. <p>If the system fails to reset, the light will remain flashing.</p>